

# ท่อหุ้มสายถัก FLEXIBLE BRAIDING CONDUIT

## ท่อหุ้มสายถัก (ฉีฉนวน) TYPE A 9133

A91330300



Certificate No. 2842125  
ISO 9002 APPROVED

- 2 Galvanized steel
- 3 Stainless steel braided #304
- 4 Stainless steel braided #430
- 5 Bronze braided



**IP50 ILFH**

- Wire-braided from conduit A2012 type.
- Inner conduit made of galvanized steel.
- Outside braid made of #304 stainless steel.
- Economic type, non-liquidtight.
- Wire braiding material available as above.

SIZE	INNER DIAMETER		OUTSIDE DIAMETER		MIN BENDING RADIUS	LENGTH OF EACH ROLL	CODE	BAHT
	min	max	min	max				
	mm	mm	mm	mm				
3/8"	12.30	12.80	16.70	17.20	35.00	50.00		
1/2"	15.80	16.30	20.40	20.90	42.00	50.00		
3/4"	20.70	21.20	25.70	26.30	51.00	50.00		
1"	26.00	26.60	31.60	32.20	62.00	50.00		
1-1/4"	34.70	35.40	40.80	41.50	85.00	30.00	สินค้าสั่งพิเศษ	
1-1/2"	40.00	40.60	46.60	47.20	99.00	30.00		
2"	51.30	51.90	57.90	58.50	121.00	20.00		
2-1/2"	63.00	63.60	72.00	72.60	145.00	15.00		
3"	78.00	78.70	87.00	87.70	180.00	15.00		
4"	101.60	102.60	110.30	111.30	230.00	10.00		

## ท่อหุ้มสายหลัก (BS TYPE) TYPE A 9333



**IP66**

- Wire-braided from conduit A2017 type.
- Inner conduit made of galvanized steel and with PVC jacketed.
- Outside braid made of #304 stainless steel wire.
- Ultra flexible and waterproof.
- Wire braiding material available as above.

SIZE	INNER DIAMETER		OUTSIDE DIAMETER		MIN BENDING RADIUS	LENGTH OF EACH ROLL	CODE	BAHT
	min	max	min	max				
	mm	mm	mm	mm				
3/8"	12.30	12.80	17.70	18.20	70.00	50.00		
1/2"	15.80	16.30	21.40	21.90	90.00	50.00		
3/4"	20.70	21.20	26.70	27.30	110.00	50.00		
1"	26.00	26.60	32.80	33.40	150.00	50.00		
1-1/4"	34.70	35.40	42.00	42.70	175.00	30.00	สินค้าสั่งพิเศษ	
1-1/2"	40.00	40.60	48.00	48.60	200.00	30.00		
2"	51.30	51.90	59.50	60.10	230.00	20.00		
2-1/2"	63.00	63.60	73.60	74.20	250.00	10.00		
3"	78.00	78.70	89.00	89.70	300.00	10.00		
4"	101.60	102.60	113.00	114.10	400.00	5.00		



**ท่อหุ้มสายถัก (EF TYPE) TYPE A 9533**



**IP66**



- Wire-braided from conduit A2067 type.
- Inner conduit made of galvanized steel and with PVC jacketed.
- Outside braid made of #304 stainless steel wire.
- Waterproof and high tension resistant.
- Wire braiding material available as page 8

SIZE	INNER DIAMETER		OUTSIDE DIAMETER		MIN. BENDING RADIUS	LENGTH OF EACH ROLL	CODE	BAHT
	min.	max.	min.	max.				
	mm	mm	mm	mm				
3/8"	12.30	12.80	18.50	19.00	75.00	50.00		
1/2"	15.80	16.30	20.00	22.50	95.00	50.00		
3/4"	20.70	21.20	27.40	27.90	120.00	30.00		
1"	26.20	26.80	33.90	34.60	180.00	30.00		
1-1/4"	34.80	35.40	42.60	43.40	230.00	20.00		
1-1/2"	40.10	40.60	48.80	49.70	270.00	20.00		
2"	51.30	51.90	60.80	61.70	300.00	15.00		
2-1/2"	63.00	63.60	73.90	74.80	350.00	10.00		
3"	78.00	78.70	89.70	90.70	500.00	10.00		
4"	101.60	102.60	115.00	116.10	650.00	5.00		

**สินค้าส่งพิเศษ**

**ท่อหุ้มสายถัก (SPIRAL TUBE) TYPE A 9833**



- Wire-braided from SPIRAL TUBE A 4013.
- Outside braid made of #304 stainless steel.
- Heavy duty design, use in hazardous locations to isolate conduit systems from vibration and movement.
- Suitable in conductors and fluids for explosion-proof and waterproof.
- Wire braiding material available as page 8

NOMINAL DIAMETER		DIAMENSION (mm)			RADIUS OF CURVATURE (mm)		WEIGHT (Kg/m)		BREAKING PRESSURE (Kg/m)	CODE	BAHT
A (mm)	B (inch)	O.D.	I.D.	T	MINIMUM BEND	REPEATED BEND	TUBE ONLY	ONE BRAID			
10	3/8"	15.5	10.0	0.25	30	125	0.17	0.32	50		
15	1/2"	19.0	13.5	0.30	40	130	0.26	0.45	50		
20	3/4"	25.5	19.0	0.30	50	180	0.32	0.57	50		
25	1"	33.0	26.0	0.30	60	200	0.40	0.70	50		
32	1-1/4"	41.0	32.5	0.35	70	240	0.60	0.95	30		
40	1-1/2"	47.5	38.0	0.40	80	320	0.85	1.43	30		
50	2"	61.5	50.5	0.40	90	380	1.25	2.05	20		
65	2-1/2"	87.5	66.0	0.40	100	400	1.44	2.31	10		
80	3"	101.5	77.5	0.40	150	420	1.92	3.11	10		
100	4"	127.5	102.5	0.40	200	450	2.40	3.80	5		

**สินค้าส่งพิเศษ**

