



MAGNETIC CONTRACTOR 3 PHASE " SC " SERIES

SC MODEL	MOTOR CAPACITY AC3 IEC947-4 (kW)		RATED CURRENT (Amp)		AUX.		COIL VOLTAGE				UNIT PRICE (BAHT)
	200-220V	380-440V	200-220V	380-440V	NO	NC	24V	120V	240V	400V	
SC-03	2.5	4	11	9	1	-	X	X	X	X	640.00
SC-0	3.5	5.5	13	12	1	-	X	X	X	X	700.00
SC-05	3.5	5.5	13	12	1	1	X	X	X	X	880.00
SC-5-1	5.5	11	22	22	1	1	X	X	X	X	126.00
SC-N1	7.5	15	32	32	2	2	X	X	X	X	1,820.00
SC-N2	11	18.5	40	40	2	2	X	X	X	X	2,420.00
SC-N2S	15	22	50	50	2	2	X	X	X	X	2,970.00
SC-N3	18.5	30	65	65	2	2	X	X	X	X	3,690.00
SC-N4	22	40	80	80	2	2	X	X	X	X	4,950.00
SC-N5	30	55	105	105	2	2	O	O	O	X	5,500.00
SC-N6	37	60	125	125	2	2	O	O	O	X	8,030.00
SC-N7	45	75	150	150	2	2	O	O	O	X	11,500.00
SC-N8	55	90	180	180	2	2	O	O	O	X	13,200.00
SC-N10	65	110	220	220	2	2	O	O	O	X	18,400.00
SC-N11	90	160	300	300	2	2	O	O	O	X	23,000.00
SC-N12	120	220	400	400	2	2	O	O	O	X	35,500.00
SC-N14	180	315	600	600	2	2	O	O	O	X	75,000.00
SC-N16	200	400	800	800	2	2	O	O	O	X	85,000.00

REMARK : " X " Coil Operating Voltage AC , " O " Coil Operating Voltage Both AC and DC

